

## SIDESHIFTS

### SIDESHIFTS

Our high visibility side shift is compatible with all truck carriages and conforms to all standards. The slim designed bars, along with high visibility, create a reduced weight. This increases lifttruck nett capacity, whilst reducing strain on the hydraulic system.

Fully adjustable  
forged  
lower hooks



- Very easy to fit and service.
- Full-width top hook protecting critical wear surfaces, resulting in longer bushing life in heavy duty applications.
- Fully replaceable wear slides made of special self-lubricating impregnated nylon with a very low-friction co-efficient.
- Cylinder rod seals are replaceable.
- Fully adjustable lower hooks.
- Delivered without fittings in the cylinder.

REF	capacity	FEM class	stroke	width	weight kg
101PM4265	2500@500	class 2	100 + 100	1400	80
101PM4266	2500@500	class 2	100 + 100	1150	64
101PM4267	2500@500	class 2	100 + 100	1100	62
101PM4131	2500@500	class 2	100 + 100	1040	60
101PM4188	2500@500	class 2	100 + 100	1020	59
101PM4268	2500@500	class 2	100 + 100	1000	59
101PM4196	2500@500	class 2	100 + 100	980	58
101PM4187	2500@500	class 2	100 + 100	920	56
101PM4269	2500@500	class 2	100 + 100	900	55
101PM4270	4900@500	class 3	100 + 100	1400	130
101PM4271	4900@500	class 3	100 + 100	1350	120
101PM4272	4900@500	class 3	100 + 100	1250	115
101PM4197	4900@500	class 3	100 + 100	1150	109
101PM4189	4900@500	class 3	100 + 100	1100	106
101PM4273	4900@500	class 3	100 + 100	1000	103
101PM4274	8000@600	class 4	100 + 100	1250	230

### SIDESHIFTS FOR REACH TRUCK



REF	capacity	FEM class	stroke	width	weight	lost load	centre of grav.
101PM4764	2500@500	class 2	100 + 100 mm	800 mm	45 kg	65 mm	35 mm